

David Tomás Sánchez Martínez
Lourdes García Rodríguez
(coordinadores)

Proceedings of the 7th International Seminar on

ORC

Power Systems

Editorial Universidad de Sevilla

Proceedings of the 7th International Seminar on

ORC

Power Systems

David Tomás Sánchez Martínez

Lourdes García Rodríguez

(coordinadores)

Proceedings of the 7th International Seminar on

ORC

Power Systems

(ORC2023)

**4th to 6th
SEPTEMBER
SEVILLE 2023**

 **eus** EDITORIAL
UNIVERSIDAD DE SEVILLA

Sevilla, 2024

Comité editorial de
la Editorial Universidad de Sevilla:

Araceli López Serena
(Directora)

Elena Leal Abad
(Subdirectora)

Concepción Barrero Rodríguez
Rafael Fernández Chacón
María Gracia García Martín
María del Pópulo Pablo-Romero Gil-Delgado
Manuel Padilla Cruz
Marta Palenque
María Eugenia Petit-Breuilh Sepúlveda
Marina Ramos Serrano
José-Leonardo Ruiz Sánchez
Antonio Tejedor Cabrera

Review chairs of the 7th International Seminar on ORC Power Systems

Prof. Christoph Wieland (University of Duisburg-Essen) - *Review Chair*

Prof. Sotirios Karellas (National Technical University of Athens) - *Review Co-Chair*

Prof. Teemu Turunen-Saaresti (LUT University) - *Review Co-Chair*

Dr. Diego-César Alarcón-Padilla (Plataforma Solar de Almería - CIEMAT) - *Review Co-Chair*

Dr. Francesco Crespi (Universidad de Sevilla) - *Review Co-Chair*

Esta obra se distribuye con la licencia

Creative Commons Atribución-NoComercial-SinDerivadas 4.0 Internacional ([CC BY-NC-ND 4.0](https://creativecommons.org/licenses/by-nc-nd/4.0/))



Usted es libre de:

Compartir — copiar y redistribuir el material en cualquier medio o formato

La licencianta no puede revocar estas libertades en tanto usted siga los términos de la licencia

Bajo los siguientes términos:

Atribución — Usted debe dar crédito de manera adecuada, brindar un enlace a la licencia, e indicar si se han realizado cambios . Puede hacerlo en cualquier forma razonable, pero no de forma tal que sugiera que usted o su uso tienen el apoyo de la licencianta.

NoComercial — Usted no puede hacer uso del material con propósitos comerciales .

SinDerivadas — Si remezcla, transforma o crea a partir del material, no podrá distribuir el material modificado.

No hay restricciones adicionales — No puede aplicar términos legales ni medidas tecnológicas que restrinjan legalmente a otras a hacer cualquier uso permitido por la licencia.

© Editorial Universidad de Sevilla 2024

c/ Porvenir, 27 - 41013 Sevilla.

Tlfs.: 954 487 447; 954 487 451; Fax: 954 487 443

Correo electrónico: info-eus@us.es

Web: <https://editorial.us.es>

© [David Tomás Sánchez Martínez](#) y [Lourdes García Rodríguez](#)
(coordinadores)

© De los textos, los autores 2024

ISBN 978-84-472-2745-7

DOI: <https://dx.doi.org/10.12795/9788447227457>

Diseño de cubierta y maquetación: los autores

INDEX OF CONTRIBUTIONS

ID3 - Additive manufacturing for fast prototyping of a velocity compounded radial re-entry turbine Authors: Dominik Stümpfl, Karel Ráž, Philipp Streit, Andreas P. Weiß.	13
ID4 - Thermodynamic concept of a novel recuperative two-phase power cycle process Authors: Benedikt G. Bederna, Riley B. Barta, Christiane S. Thomas.	23
ID7 - Performance analysis of a 1.5 MW Organic Rankine Cycle in a Carnot battery system for grid balancing services Authors: Robin Tassenoy, Hannes Van De Velde, Kenny Couvreur, Michel De Paepe, Steven Lecompte.	33
ID8 - Calibration of multi-hole probes for measurements in compressible organic vapor flows Authors: Leander Hake, Stephan Sundermeier, Stefan Aus Der Wiesche, Maximilian Passmann.	43
ID9 - pocketORC: A browser-based calculator for teaching organic Rankine cycle power systems Authors: Martin White.	53
ID10 - Evaluation of existing supercritical heat transfer correlations for designing the vapor generator in low-temperature transcritical Organic Rankine Cycle systems Authors: Jera Van Nieuwenhuyse, Anastasios Skiadopoulos, Dimitris Manolakos, Steven Lecompte, Michel De Paepe.	61
ID12 - A novel combined cooling and power cycle integrated ejector refrigeration and composition adjustment for stationary engine waste heat recovery Authors: Xiaocun Sun, Lingfeng Shi, Hua Tian, Gequn Shu.	71
ID14 - Design and construction of a reversible ORC test rig for geothermal CHP applications Authors: Florian Kaufmann, Christopher Schiffler, Christoph Wieland, Hartmut Spliethoff.	81
ID15 - Robust and fast meanline methodology for radial inflow turbines with non-ideal gases for system level optimisation of organic Rankine cycles Authors: Carola Freytag, Eva Alvarez-Regueiro, Pablo Ale-Martos, Esperanza Barrera-Medrano, Ricardo Martinez-Botas.	91
ID16 - Shape optimization of a sCO ₂ centrifugal compressor stage Authors: Alessandro Romei, Paolo Gaetani, Giacomo Persico.	101
ID17 - Optimizing the performance of a hybrid solar-biomass micro-CHP system with a TFC engine as the prime mover for domestic applications Authors: Anastasios Skiadopoulos, Xander Van Heule, Steven Lecompte, Michel De Paepe, Dimitrios Manolakos.	109
ID19 - Systematic and multi-criteria optimisation of subcritical thermally integrated Carnot batteries (TI-PTES) in an extended domain Authors: Antoine Laterre, Olivier Dumont, Vincent Lemort, Francesco Contino.	119

ID20 - ORC technology used in a heat removal system for an advanced nuclear power plant Authors: Guillaume Lhermet, Benoit Payebien, Nicolas Tauveron, Nadia Caney, Franck Morin	130
ID22 - Assessment of trilateral Organic Rankine Cycle for solar applications with innovative turboexpander concept Authors: Alessandro Romei, Andrea Giostri, Andrea Spinelli.	140
ID25 - Evaluation of the performance of an axial one-stage 10kW turbogenerator through experimental testing Authors: Piotr Klimaszewski, Piotr Klonowicz, Lukasz Witanowski, Tomasz Suchocki, Piotr Lampart, Eugeniusz Ihnatowicz, Lukasz Antczak, Dawid Zaniewski, Lukasz Jedrzejewski	149
ID26 - Investigation of the turbulence level and the vortex shedding in a turbine cascade working with an organic vapor at subsonic Mach numbers Authors: Leander Hake, Stephan Sundermeier, Stefan Aus Der Wiesche, Camille Matar, Paola Cinnella, Xavier Gloerfelt	159
ID27 - A novel approach to district heating: using a two-phase expander in a reversible heat pump-Organic Rankine Cycle system Authors: Sindu Daniarta, Attila R. Imre, Piotr Kolasinski	169
ID28 - Optimization of a partially evaporating Organic Rankine Cycle with thermal non-equilibrium expansion Authors: Xander Van Heule, Tasos Skiadopoulos, Dimitris Manolakos, Michel De Paepe, Steven Lecompte	176
ID29 - Cost-effective option of cold energy utilization in pharmaceutical industry Authors: Sindu Daniarta, Dawid Sowa, Ádám Havas, Attila R. Imre, Piotr Kolasinski	184
ID30 - Numerical investigation of a transonic dense gas flow over an idealized blade vane configuration Authors: Aurelien Bienner, Xavier Gloerfelt, Paola Cinnella, Leander Hake, Stefan Aus Der Wiesche	193
ID31 - Comprehensive analysis of ORC-VCC system for air conditioning from low-temperature waste heat Authors: Lukasz Witanowski	203
ID33 - Pareto front analysis for the design and the working fluid selection in ORC-based pumped thermal energy storage technology in both pure electric and cogenerative applications Authors: Marco Astolfi, Dario Alfani, Andrea Giostri	214
ID36 - Evaluating the waste heat sources in a very large crude carrier and the potential integration of Organic Rankine Cycle configurations Authors: Amalia Stainchaouer, Christopher Schiffler, Christoph Wieland, Hartmut Spliethoff	224
ID37 - Investigating R1234ze and R1234yf as replacements to R134a in waste heat recovery ORC applications Authors: James Bull, James Buick, Jovana Radulovic	234

ID38 - Performance and economic assessment of a thermally integrated reversible HP/ORC Carnot battery applied to data centers Authors: Chiara Poletto, Andrea De Pascale, Saverio Ottaviano, Olivier Dumont, Maria Alessandra Ancona, Michele Bianchi	244
ID39 - Evaluation of the performance of multiple supercritical CO ₂ power cycles in Waste Heat Recovery applications Authors: Hicham Chibli, Matthew Read, Abdalnaser Sayma	254
ID40 - Design and modeling of a demonstration-scale ORC cycle for the Liquid Air Combined Cycle Authors: Owen Pryor, William Conlon, Aaron Rimpel, Milton Venetos.....	264
ID41 - Guidelines and optimization criteria of a machine learning-based methodology for mixture design in ORC systems Authors: Valerio Mariani, Saverio Ottaviano, Andrea De Pascale, Giulio Cazzoli, Lisa Branchini, Gian Marco Bianchi	273
ID45 - Potential of trigenerative Waste Heat Recovery CO ₂ -mixture transcritical power plants for increasing the sustainability of district heating and cooling networks Authors: Mattia Baiguini, Michele Doninelli, Ettore Morosini, Dario Alfani, Gioele Di Marcoberardino, Paolo Giulio Iora, Giampaolo Manzolini, Costante Mario Invernizzi, Marco Astolfi	282
ID46 - Thermodynamic analysis of a novel pumped thermal energy storage system with waste heat integration Authors: Meiyang Zhang, Lingfeng Shi, Peng Hu, Gang Pei, Gequn Shu	294
ID48 - Pressure profile optimisation of a nozzle for wet-to-dry expansion Authors: Pawel Ogrodniczak, Abdalnaser Sayma, Martin T. White.....	304
ID51 - Thermodynamic modification of CO ₂ -based combined cooling and power cycle with ejector Authors: Yonghao Zhang, Lingfeng Shi, Gequn Shu	313
ID53 - Selection of suitable working fluid and storage material for ORC coupled with Thermal Energy Storage Authors: Dawid Sowa, Sindu Daniarta, Piotr Kolasinski	323
ID54 - Influence of dopant fluorination on the heat transfer behaviour of CO ₂ -based mixtures in transcritical power cycles Authors: Michele Doninelli, Gioele Di Marcoberardino, Costante Mario Invernizzi, Paolo Giulio Iora	333
ID57 - On air-cooled condensers for ORC systems operating with zeotropic mixtures Authors: Lorenzo Galieti, Carlo De Servi, Dario Alfani, Paolo Silva, Paola Bombarda, Piero Colonna	344
ID58 - Experiments on supersonic ORC nozzles in linear cascade configuration Authors: Marco Olivetti, Marco Manfredi, Giacomo Persico, Andrea Spinelli, Paolo Gaetani, Vincenzo Dossena	354
ID59 - Numerical analysis of aerodynamics and performance of a radial-inflow micro-ORC turbine Authors: Fatemeh Ardaneh, Marta Zocca, Antti Uusitalo, Teemu Turunen-Saaresti.	363

ID61 - ORC system using R1233zd(E) for waste heat recovery from the upstream process Authors: Meng Soon Chiong, Bemgba Nyakuma, Nur Izwanne Mahyon, Srithar Rajoo, Eva Alvarez-Regueiro, Maria Esperanza Barrera-Medrano, Ricardo F. Martinez-Botas, Yossapong Laoonual	373
ID63 - Experimental investigation of a small-scale reversible high temperature heat pump – Organic Rankine Cycle system for industrial Waste Heat Recovery Authors: Rahul Velanparambil Ravindran, Donal Cotter, Christopher Wilson, Ming Jun Huang, Neil Hewitt.	381
ID64 - Technical comparison and evaluation of a Pumped Thermal Energy Storage with two different designs Authors: Márcio Santos, Jorge André, Ricardo Mendes, José Ribeiro.	391
ID68 - The potential of CO ₂ -Plume Geothermal (CPG) Systems for CO ₂ component manufacturers: opportunities and development needs Authors: Christopher Schiffelechner, Jasper De Reus, Hartmut Spliethoff, Martin O. Saar, Sebastian Schuster, Dieter Brillert	400
ID69 - Development of a generalised low-order model for twin-screw compressors Authors: Florian Kaufmann, Ludwig Irrgang, Christopher Schiffelechner, Hartmut Spliethoff.	410
ID71 - Decision-making matrix for the selection of mixture in ORC applications Authors: William Combaluzier, Nicolas Tauveron, Michel Beaughon, Aldo Serafino.	420
ID72 - Reversible heat pump-ORC pilot plant – Experimental results and fluid charge optimization Authors: Maximilian Weitzer, Sebastian Kolb, Dominik Müller, Jürgen Karl	430
ID73 - Performance of Organic Rankine Cycle system in combination with residual municipal solid waste gasification: a simulation analysis Authors: Luca Cioccolanti, Giovanni Biancini, Ramin Moradi, Luca Del Zotto, Matteo Moglie	439
ID74 - Enhancing knowledge of engineering students at all levels on organic rankine cycle systems for their application in the built environment Authors: Luca Cioccolanti, Ramin Moradi, Ermira Abdullah, Syamimi Saadon, Mohamad Yusof Idroas, Teoh Yew Heng, Kwanchai Kraitong	449
ID75 - Studying carbon dioxide and acetone mixtures in a single-stage absorption-compression cycle for heating and cooling applications Authors: Jesús Gómez-Hernández, Ali Kholghi, Mercedes De Vega, Javier Villa, Ronan Grimes	458
ID77 - Valorising thermal composite recycling processes using Organic Rankine Cycles for combined heat and power applications Authors: Ramin Moradi, Liu Yang	466
ID80 – Prediction of the ideal maximum operational temperature of hydrocarbon and HFCs as working fluids of Organic Rankine Cycle power plants based on transition state theory Authors: Wei Yu, Chao Liu, Xijie Ban, Zhirong Li, Tianlong Yan	476
ID82 - Comparison of different evaporator topologies for industrial heat pumps Authors: Sanjay Vermani, Nitish Anand, Johan Van Bael, Evgueni Toulankine, Aldo Serafino, Carlo De Servi.	486

ID83 - On the plant improvement of Solar-driven ORC based power unit for domestic microcogeneration Authors: Fabio Fatigati, Marco Di Bartolomeo, Arianna Coletta, Diego Vittorini, Giammarco Di Giovine, Davide Di Battista, Roberto Cipollone.	496
ID84 - Mapping the techno-economic potential of next-generation CSP plants running on transcritical CO ₂ -based power cycles Authors: Pablo Rodríguez-deArriba, Francesco Crespi, Sara Pace, David Sánchez	505
ID86 - Achieving 45% micro gas turbine efficiency through hybridization with Organic Rankine Cycles Authors: Antonio Escamilla, David Sánchez Martínez, Lourdes García-Rodríguez	515
ID88 - Operational optimisation of the main heat rejection unit of CSP plants based on carbon dioxide mixtures Authors: Francesco Crespi, Pablo Rodríguez-deArriba, Lourdes García-Rodríguez, David Sánchez.	525
ID89 - Mechanical design and rotor-dynamic analysis of the ORCHID turbine Authors: Matteo Majer, Steven Chatterton, Ludovico Dassi, Alessio Secchiaroli, Edoardo Gheller, Carlo De Servi, Paolo Pennacchi, Piero Colonna, Matteo Pini.	535
ID91 - Thermodynamic feasibility of a pumped thermal energy storage driven by ocean temperature gradient Authors: Alessandra Ghilardi, Andrea Baccioli, Guido Francesco Frate, Lorenzo Ferrari	545
ID92 - Exergy-based methods for heat pumps Authors: Mathias Hofmann, Jonas Freißmann, Malte Fritz, Jeremias H. Alexe, Francesco Witte, George Tsatsaronis	553
ID93 - Reduced order modelling of optimized heat exchangers for maximum mass-specific performance of Airborne ORC Waste Heat Recovery units Authors: Fabio Beltrame, Dabo Krempus , Piero Colonna, Carlo De Servi.	563
ID97 - Basic design of an ORC demonstrator system for implementation in an Iron & Steel plant through the DECAGONE project Authors: Magnus Windfeldt, Han Deng, Trond Andresen, Christopher Schiffler	574
ID98 - Analytical estimation of the presence of non-condensable gases in the condensate tank of an Organic Rankine Cycle Authors: Radheesh Dhanasegaran, Antti Uusitalo, Juha Honkatukia, Teemu turunen-Saaresti	584
ID101 - Advanced control of compressor inlet temperature in supercritical CO ₂ Brayton cycle Authors: Rui Wang, Xuan Wang, Hua Tian, Gequn Shu.	596
ID103 - Potential for surplus-heat-to-power conversion in current and future aluminium production processes with off-gas recycling Authors: Jonas Bueie, Magnus Windfeldt, Trond Andresen.	605
ID104 - Investigating the application range of ORC power plants for the exploitation of two-phase geothermal resources Authors: Tristan Merbecks, Claudio Pietra, Paola Bombarda, Martin O. Saar, Paolo Silva, Dario Alfani.	615
ID109 - Cold Energy Recovery in LNG plants with Organic Rankine Cycle Authors: Gabriele Marchiori, Marta Giudici, Giorgia Ruffato, Marco Astolfi	626

ID110 - Numerical investigation of organic vapor flow effects on a micro-scale radial turbocompressor Authors: Andrés Sebastián, Rubén Abbas, Manuel Valdés	636
ID112 - Design, modeling and simulation of an experimental Rankine PTES system Authors: Mario Petrollese, Giorgio Cau, Matteo Marchionni, Marcello Lorenzo Marroccu, Rosa Merchan	645
ID113 - Small-scale turbopumps for Waste Heat Recovery applications based on an Organic Rankine Cycles, modeling, analytical and experimental investigation Authors: Sajjad Zakeralhoseini, Jürg Schiffmann	655
ID116 - Double-stage ORC system based on various temperature waste heat sources of the negative CO2 power plant Authors: Kamil Stasiak, Pawel Ziolkowski, Dariusz Mikielewicz	665
ID117 - Optimization of organic Rankine cycle in ocean thermal energy conversion based on NSGA-II Authors: Zheng Hu, Jiufa Chen, Bing Guo, Chengbin Zhang	679
ID118 - TES4Trig: Development of a demonstrator for the production of electricity, heating and cooling based on an Organic Rankine and an Ejector Cooling Cycle driven by high-temperature parabolic trough collectors with thermal energy storage Authors: Konstantinos Braimakis, Dimitrios Tziritas, George Stavrakakis, Julio Terrón Gutiérrez, Siddhart Dutta, Christos Xynos, Panagiotis Zervas, Sotirios Karellas	689
ID119 - Simulation and operation of a CSP that works with a HRB Cycle Authors: Antonio J. Subires, Antonio Rovira	701
ID123 - Towards a green energy community: integration of micro-ORCs combined with renewable energy technologies in buildings Authors: Diego Antonio Rodríguez Pastor, Víctor Manuel Soltero Sánchez, Elisa Carvajal Trujillo, José Antonio Becerra, Ricardo Chacartegui	713
ID129 - Assessment of high temperature heat pump layouts equipped with a bladeless turboexpander Authors: Matteo Passalacqua, Simone Maccarini, Stefano Barberis, Alberto Traverso	723
ID133 - Selection of the optimal working fluid in an Organic Rankine Cycle for Waste Heat Recovery through multi-objective optimization and decision making Authors: Bipul Krishna Saha, El Mouatez Billah Messini, Syed J. Hoque, B Aneesh Bhat, Pramod Kumar	733
ID139 - Dual condensing pressure ORC for cryogenic energy storage Authors: William M. Conlon, Milton J. Venetos	743
ID141 - Optimum coupling of thermal energy storage and power cycles for Carnot batteries Authors: Salvatore Guccione, Rafael Guede	751
ID142 - Aerodynamic design and numerical analysis of a counter-rotating centrifugal compressor Authors: Cheikh Brahim Abed, Arthur Leroux	761

Evaluation of the performance of an axial one-stage 10kW turbogenerator through experimental testing

Piotr Klimaszewski^{1,*}, Piotr Klonowicz¹, Łukasz Witanowski¹, Tomasz Suchocki¹, Piotr Lampart¹, Eugeniusz Ihnatowicz², Łukasz Antczak², Dawid Zaniewski², Łukasz Jedrzejewski²

¹*Institute of Fluid-Flow Machinery, Polish Academy of Sciences, Gdansk, Poland*

²*MARANI Sp. z o.o., Zabrze, Poland*

*Corresponding Author: pklimaszewski@imp.gda.pl

ABSTRACT

The paper describes the results of experimental research on a prototype one-stage turbo-generator with a nominal power of 10 kW and a rotational speed of 24 000 rpm. The expander at the Institute of Fluid-Flow Machinery, Polish Academy of Sciences was developed as part of the R&D project with Marani company. The unit construction consists of an overhanging rotor and shaft mounted on rolling bearings. The turbo-generator was tested on a specially constructed laboratory test stand in the first stage. Compressed air instead of refrigerant gas (R1233zd) was used. The test results converged with the parameters obtained using the RANS simulation. The convergence for the turbine mass flow was 97% of the value obtained in the CFD model, which is satisfactory. The power generated by the turbo-generator, which was compared at this stage, also achieved satisfactory convergence (95% to 97%) with the calculation model. These tests allowed determine the compliance of the adopted design assumptions and confirmed the correctness of the calculation tools used. The next stage of work was to examine the ORC unit in operating conditions. That stage was aimed at checking the correct work of the machine with the ORC system. The turbine achieved internal efficiency calculated from temperatures at a level slightly lower than that obtained from numerical calculations (total-to-static efficiency). The efficiency was equal to about 73%, and the difference between calculated and measured values do not exceed 0.25 pp. (percentage point). The electric efficiency was about 65% and a maximum electric power output of 6.8 kW was measured.

149

1 INTRODUCTION

The rise in energy consumption over the past century has led to increased emissions of greenhouse gases, subsequently resulting in a rise in global temperatures. Continuing on this trajectory could yield detrimental effects, such as escalating destructive weather phenomena (Ramanathan and Feng, 2009). The industry sector was one of the first to enact climate regulations, with various sectors having unique methods for reducing CO₂ emissions. Particularly in steel and aluminium production, waste heat recovery presents an ideal opportunity to boost overall process efficiency.

The Organic Rankine Cycle (ORC) technology has emerged as a promising solution to facilitate energy recovery from waste heat within the industry. ORC systems are specifically engineered to synergize with industrial apparatuses such as compressors, large engines, or various eco-friendly technologies. The fundamental components of ORC systems include a turbine, pump, condenser, and evaporator. These systems operate based on the Organic Rankine Cycle. The fluids utilized in this context differ from water and include, for instance, hydrocarbons and refrigerants. The fluid selection process was thoroughly described by (Klimaszewski *et al.*, 2019).

ORC turbine design offers a fertile ground for optimization. The rotor and stator geometry can be numerically analyzed using specialized software. Various publications address this issue. (Witanowski

et al., 2023) presented the Nelder-Mead optimization of a single-stage axial turbine in their paper. The turbine, functioning within the ORC system, utilized R7100 as the working fluid. The optimization results were promising, with the total-to-static efficiency of the new geometry increasing by about 5.5 percentage points at the design point.

An alternate approach involves optimizing the ORC turbine to operate in two distinct work modes: for parameters appearing in cogeneration and condensation mode. A multi-objective optimization for a turbine working with MM was conducted by (Witanowski *et al.*, 2023). The authors identified a flow path with improved efficiency using the Implicit Filtering algorithm. A substantial efficiency increase of 4.8 percentage points was observed in the cogeneration mode, and in the cogeneration mode turbine efficiency, it increased by about 3.1 percentage points. Another significant approach in the optimization field involves hybrid algorithms, as the blade shape optimization geometry discussed (Witanowski *et al.*, 2023).

Authors of various publications have conducted experimental tests on ORC turbines, either on a test stand or as part of an ORC system. Kang, S. H. (Kang, 2016) describes preliminary tests of an ORC turbine coupled with an ORC system. The working fluid was R245fa. A two-stage radial expander was used, with the generator directly connected to the turbine. The installation achieved a maximum electric power of 39 kW, a cycle efficiency of 9.8%, and turbine efficiency based on output equal to 58.4%. The author highlighted the potential for further efficiency improvements via the reduction of heat and pressure losses.

The article (Fu *et al.*, 2015) details an ORC system designed for an electric power output of 250 kW. The preliminary test results were quite satisfactory. The system achieved a maximum net power output of approximately 219.5 kW, a maximum thermal efficiency of 7.94%, and a turbine speed of 12,386 RPM, with an isentropic efficiency equal to 63.7%. The working fluid used was the refrigerant R245fa. The power generated by the turbine was transferred to the generator via a gearbox, with the electric generator maintaining a rotational speed of 3600 RPM.

The authors of the publication (Borsukiewicz-Gozdur, 2013) outlines experimental research conducted on an ORC power plant. The ORC installation was designed to operate with a geothermal heat source, with hot water temperatures ranging from 66°C to 111°C. The experiment also involved a hermetic turbine working with R227ea fluid as part of the ORC system. The turbine generator was designed for a rotational speed of 3000 RPM, a standard value in the power grid. The electric efficiency of the ORC system was approximately 4.88%.

2 TEST STAND

The test stand was built in the laboratory of the Institute of Fluid Flow Machinery Polish Academy of Sciences. The turbine (no. 2 in Figure 1) was mounted on the test stand. The test stand consists of a compressor connected with an air heater and flow meter (no. 1 in Figure 1), a system of valves for fluid control connected by pipelines (no. 4 in Figure 1), a generator cooling system (no. 5 in Figure 1). The measuring system includes pressure sensors and thermocouples (no. 6 in Figure 1) that elements are connected to a device for data collection. The mobile measurement instruments were used to control the machine's mechanical vibrations and the shaft's displacement.




Figure 1 Turbine 10 kW on a test stand, 1-compressor, 2-turbine, 3- feed pipeline, 4 - control valves, 5 – cooling system, 6 – pressure transmitter, 7- turbine outlet.

The ORC turbine was designed to work with R1233zd, a refrigerant with low global warming and ozone deployment potential. The 10 kW turbine investigation on the test stand was carried out with substitute medium - air. The main reason for using air instead of R1233zd on the laboratory test stand was the complexity of building a system for testing with refrigerant. At this stage, the primary goal was to test the mechanical construction, specifically the vibration level in the x-axis. The test stand allows also to check of the mechanical working parameters of the turbine and check the quality of fabrication flow system elements.

151

The installation works as follows: compressed air goes by pipelines from the compressor to the heater, and hot air is divided into two streams for the left and right inlets on a turbine. The outlet is open, the air goes to atmospheric conditions. The pipeline delivering fluid to the turbine was marked as no. 3 in Figure 1, the turbine outlet was shown as no. 7 in Figure 1. The fluid flow throw machine was controlled, the parameters like temperature, pressure and mass flow were measured and analysed. The laboratory installation includes the main cycle five pressure and five temperature sensors.

The test stand also includes a separate cooling water system used for generator cooling (more details were described in the article (Zaniewski *et al.*, 2023)).

The power system consists of a water resistor and an electro-energetic converter for controlling electric power parameters.

3 10 KW TURBO-GENERATOR TESTS

Tests in the laboratory consist of three phases. The first phase include a direct load of the turbogenerator, the water resistor was directly connected to the turbine generator, and the electric load was controlled by the mechanical movement of elements. When the parameters of the research were satisfied then, the next phase include the use electro-energetic device. The device connects the turbogenerator with the electric grid indirectly, allow also to control its work parameters. In the second phase electronic device was used to connect indirectly with a water resistor. In the third phase, the connection was prepared to an electro-energetic grid.

The observed parameters were static pressure on an inlet, total temperature on the inlet, the total temperature on the outlet, mass flow, rotation speed and electric power.

In that part of the investigation, parallel conduct tests of vibrations parameters were conducted (Figure 2). Necessary to define the quality of the mechanical work of a machine. All tests were achieve satisfied values and did not exceed recommend values for that kind of micro-turbines. The recommended values

are based on the standard ISO 20816 (Industrial machinery with a power rating above 15 kW and operating speeds between 120 r/min and 30 000 r/min).




Figure 2 The amplitudes of vibration acceleration in the Y axis for the frequency spectrum up to 12000 Hz recorded for the speed of 6000 rpm (upper graph) and the nominal speed of 24000 rpm (lower graph) respectively.

The amplitudes of vibration acceleration in the X axis for the rotational speed of 6000 rpm and 24000 rpm are shown. The peak values achieved at nominal speed are an order of magnitude higher than at much lower rotational speeds.

4 CFD RESULTS ANALYSIS COMPARED TO EXPERIMENTAL RESULTS

The CFD calculations were used to verify experimental results. The mathematical model was solved with the use of CFD methods. Numerical methods include the body's inlet domain and the diffuser's outlet domain. The additive losses connected with bearing and windage were also included.

The mesh was present in Figure 3. The computational mesh was prepared with Ansys Turbogrid and ICEM software. The mesh domain includes a rotor and stator consisting of 26 629 378 elements and 28 430 740 nodes, the mesh is hexahedral. The area with more density mesh includes the rotor and stator, that area was the most important for calculations of fluid flow and boundary layers. The stator mesh domain includes 4 644 640 nodes and 4 227 440 elements. The rotor domain includes 10 850 840 nodes and 10 107 860 elements.

The Ansys CFX code uses the RANS equations with the $k-\omega$ SST turbulence model to describe fluid dynamics. The finite volume method with a second-order discretization scheme is used to solve these equations. The inlet boundary conditions include total pressure, total temperature, and flow direction. The outlet boundary condition is the average static pressure. The frozen rotor technique, also known as the multiple reference frame method, is used to handle the stationary stator domain and the moving rotor domain.

The total pressure on the inlet domain used for calculation was equal to 1.82 bar and the total temperature was set at 45.3°C, the turbulence was on the medium intensity (5%). The analysis performed in this study was stationary, with a constant rotor speed equal to 13,700 rpm. The

experimental and simulation results were compared and it was assumed that the fluid used in the simulation was air, modelled as an ideal gas. On the outlet domain, relative pressure was equal to 1.027 bar and the pressure profile blend was set as 0.05.




Figure 3: Computation mesh, visible an area with high density




Figure 4: Streamlines for nominal works parameters.

The streamlines were presented in Figure 4. The area with higher velocity is marked by red colour. The lower speed is shown by blue colour. The flow throws the rotor and stator correctly and in line with the assumptions. The highest speed was observed at the stator outlet. The streamlined figure on the impeller area does not appear incorrect phenomenon. That means the flow system was correctly designed. The pre-processing was conducted with the use of Ansys CFX pre-processor, and numerical calculations were conducted with the use of Ansys CFX solver.




Figure 5 Electric power achieve in the experiment in the function of rotational speed comparison to functions of rotation speed for choosing numerical models.

The results of numerical calculations and experimental data were presented in Figure 5. The convergence for nominal parameters was on the satisfied level, for low values of rotation speed was equal to 97% for high 95%. The electrical efficiency of the generator was equal to 94%. The electrical efficiency value was determined based on the information provided in the technical documentation of the electric generator and energy conversion system. This value also takes into account the losses that result from the experience of the Institute of Fluid Flow Machinery team. By considering both the documented specifications and the team's expertise, a comprehensive assessment of the electrical efficiency was achieved. The red points describe the results of the experiment, the blue points show the results of CFD calculation considering losses in bearings and friction losses values, and the orange points includes also electrical losses. The achieved values of CFD calculations include the domain of the full stator domain and rotor domain.

5 THE RESULTS OF TURBINE TESTS ON THE ORC UNIT SYSTEM

The next stage of tests was a laboratory test of the ORC unit with conditions similar to industrial. The turbine was mounted in the ORC installation, the pipelines of the inlet and outlet were connected, and the measured devices were calibrated. The tests of the turbine were conducted on the designed, working fluid R1233zd. The tests of ORC installation were conducted in the laboratory in controlled conditions. The heat was assured by the heating system based on the gas boiler. The main object of the experiment was the turbine (Figure 6 no.1). The control of the cycle parameters was assured by the pump (Figure 6 no.2), flow meter (Figure 6 no.5), control valve (Figure 6 no.4) and heat exchanger (Figure 6 no.3). The level of vibration does not exceed safety values. Measured parameters of fluid flow in the different points of the fluid system confirmed the correction of calculation. The construction was hermetic, there are no appear leakages or other unexpected damages.




Figure 6 Turbine installed on ORC plant, 1 – turbine, 2 – feed pump, 3 – heat exchanger, 4 – control valves, 5 – flow meter.

The third stage of tests was conducted in industrial conditions. The ORC system was connected to an air compressor, and the hot compress air was a source of waste heat. The data for parameter calculation were collected based on the sensor system. Sensors, similar to the preview stage of the experiment measured different parameters on the ORC loop like temperature, pressure and mass flow. The data from sensors allow for calculating the efficiency of the turbine and ORC cycle. The efficiency was calculated with the use of different parameters, first base on temperature calculation, second base on power generated by water resistor, and third base on power achieve in electro energetic system. The first method get the best results and efficiency was the highest, the value was equal to about 72%. In that method, temperature and pressure values were used to find the enthalpy value for fluid. Then based mass flow was calculated efficiency with the use of Equation (1). The efficiency calculated by the second method achieve a value of about 60%, the third method get the worse results, and the efficiency was about 57%. The changes in efficiency in the function of time was presented in Figure 7.

$$\eta_t = \frac{h_1 - h_2}{h_1 - h_{2s}} \quad (1)$$

The efficiency of the ORC cycle was presented in Figure 8. The chart presents a change in the efficiency of the function of time. The ORC cycle efficiency achieves the highest value base on the temperature measurements. A description of the calculation method of cycle efficiency was present in Equation (2). This equation also takes into account the loss parameter, including pump energy consumption, pipe

losses, and more. The calculation base on the temperature achieves a value of 6%. The temperature of hot water, the source of heat for ORC installation, was equal to 74°C on the evaporator inlet. The temperature of cooling water, at the condenser inlet was equal to 12°C. The second efficiency taking into account the process of energy conversion and electrical losses achieved a value of about 4.6%.

$$\eta_c = \frac{\dot{m}(h_2 - h_1)}{Q_s} - P_{AX} \quad (2)$$

The peaks visible on the charts result from the unstable work of the heat source. The industrial tests get satisfactory results. The main goals were achieved.




Figure 7 Efficiency of the turbine based on data from different measurement systems.




Figure 8 The ORC cycle efficiency base on different source

6 CONCLUSIONS

In this study, a three-phase experimental approach was employed to assess the performance and efficiency of a turbine incorporated into an ORC unit. This procedure involved independent turbine evaluations, laboratory tests, and full-scale industrial testing. The following conclusions summarize the key findings from the investigation.

- The experiment proceeded in three distinct stages. Initially, tests were conducted to disconnect the turbine on a dedicated test stand. Subsequently, laboratory tests were carried out to evaluate the turbine mount integrated with the ORC unit. The final phase encompassed testing the ORC unit within an industrial setting.
- The standalone turbine tests delivered satisfactory results, generating an electric power output of approximately 9 kW and achieving a rotor speed of 24,000 RPM.
- The second phase of testing proved equally successful. The primary focus was on examining the mechanical connections and operating parameters of the turbine when coupled with the ORC system under laboratory conditions. The results aligned with the predictions, with the observed data closely matching the CFD simulation values.
- The ORC unit exhibited satisfactory performance during the industrial testing phase, achieving an efficiency rating of approximately 4.6%.
- Based on the empirical data collected, it is concluded that the machine operates optimally in terms of field flow efficiency.

NOMENCLATURE

h_1	enthalpy on turbine inlet	[kJ/kg]
h_2	enthalpy on turbine outlet	[kJ/kg]
h_{2s}	isentropic enthalpy	[kJ/kg]
$\dot{m}$	mass flow	[kg/s]
P_{AX}	cycle losses	[-]
Q_s	heat source	[kJ/s]
η_c	efficiency of the cycle	[-]
η_t	efficiency of the turbine	[-]

157

REFERENCES

- Zaniewski, D., Klimaszewski, P., Klonowicz, P., Witanowski, Ł., Lampart, P., Jędrzejewski, Ł., Suchocki, T. (2023). Organic Rankine cycle turbogenerator cooling – Optimization of the generator water jacket heat exchange surface. *Applied Thermal Engineering*, 223(January), 120041. <https://doi.org/10.1016/j.applthermaleng.2023.120041>
- Witanowski, Ł., Ziółkowski, P., Klonowicz, P., Lampart, P. (2023). A hybrid approach to optimization of radial inflow turbine with principal component analysis. *Energy*, 272(January). <https://doi.org/10.1016/j.energy.2023.127064>
- Witanowski, Ł., Klonowicz, P., Lampart, P., Ziółkowski, P. (2023). Multi-objective optimization of the ORC axial turbine for a waste heat recovery system working in two modes: cogeneration and condensation. *Energy*, 264(October 2022), 126187. <https://doi.org/10.1016/j.energy.2022.126187>
- Witanowski, Ł., Klonowicz, P., Lampart, P., Klimaszewski, P., Suchocki, T., Jędrzejewski, Ł., Zaniewski, D., Ziółkowski, P. (2023). Impact of rotor geometry optimization on the off-design ORC turbine performance. *Energy*, 265(December 2022), 126312. <https://doi.org/10.1016/j.energy.2022.126312>
- Ramanathan, V., Feng, Y. (2009). Air pollution, greenhouse gases and climate change: Global and regional perspectives. *Atmospheric Environment*, 43(1), 37–50.
- Klimaszewski, P., Zaniewski, D., Witanowski, Ł., Suchocki, T., Klonowicz, P., Lampart, P. (2019). A case study of working fluid selection for a small-scale waste heat recovery ORC system. *Archives of Thermodynamics*, 40(3), 159–180. <https://doi.org/10.24425/ather.2019.129999>
- Kang, S. H. (2016). Design and preliminary tests of ORC (organic Rankine cycle) with two-stage radial turbine. *Energy*, 96, 142–154. <https://doi.org/10.1016/j.energy.2015.09.040>
- Fu, B.-R., Lee, Y.-R., Hsieh, J.-C. (2015). Design, construction, and preliminary results of a 250-kW

organic Rankine cycle system. *Applied Thermal Engineering*, 80, 339–346.
<https://doi.org/10.1016/j.applthermaleng.2015.01.077>

Borsukiewicz-Gozdur, A. (2013). Experimental investigation of R227ea applied as working fluid in the ORC power plant with hermetic turbogenerator. *Applied Thermal Engineering*, 56(1–2), 126–133. <https://doi.org/10.1016/j.applthermaleng.2013.03.039>

ACKNOWLEDGEMENT

This work has been founded by The National Centre for Research and Development and from The Smart Growth Operational Programme (European funds) within the project No. POIR.01.01.01-00-0512/16 carried out jointly with the Marani Company.

This book contains the compilation of works contributed to the *7th International Seminar on Organic Rankine Cycle Power Systems* (ORC 2023), held in Seville between the 4th and 6th of September 2023. The event was hosted by Universidad de Sevilla on behalf of the Knowledge Centre on Organic Rankine Cycle Technology (KCORC), incorporated in The Netherlands.

The ORC conference, organized biennially, stems as the only conference that is specific to ORC technology, therefore gathering a diverse community whose affiliation spans across all the interested stakeholders, not only in this particular technology but also and in a broader context, in the energy transition. Original equipment manufacturers, professional associations, end-users, investors, policy makers, academics, scientists feel at home at ORC 2023.

The almost 100 proceedings in this book cover a wide variety of topics, from fundamentals to system integration through component design, accounting for thermodynamic performance as well as component design. In addition to this, and as a new track in 2023, works on heat pump technology were also accepted in order to raise awareness of the strong ties between both technologies, specifically in energy storage applications.

This book provides an excellent overview of the current maturity of power systems based on Organic Rankine Cycle technology for applications as diverse as geothermal and waste heat recovery in industry or downstream of other prime movers (e.g., marine applications). It is also an excellent source of information to understand the current challenges faced by the technology, stemming from a very competitive market and increasingly stringent environmental regulations.

The organizers of ORC 2023 hope that the reader finds this work as exciting as the attendees to the conference and, maybe, make the decision to join the 8th edition to the conference in 2025.