

David Tomás Sánchez Martínez
Lourdes García Rodríguez
(coordinadores)

Proceedings of the 7th International Seminar on

ORC

Power Systems

Editorial Universidad de Sevilla

Proceedings of the 7th International Seminar on

ORC

Power Systems

David Tomás Sánchez Martínez

Lourdes García Rodríguez

(coordinadores)

Proceedings of the 7th International Seminar on

ORC

Power Systems

(ORC2023)

4th to 6th

SEPTEMBER

SEVILLE 2023

 **EDITORIAL**
UNIVERSIDAD DE SEVILLA

Sevilla, 2024

Comité editorial de
la Editorial Universidad de Sevilla:

Araceli López Serena
(Directora)

Elena Leal Abad
(Subdirectora)

Concepción Barrero Rodríguez
Rafael Fernández Chacón
María Gracia García Martín
María del Pópulo Pablo-Romero Gil-Delgado
Manuel Padilla Cruz
Marta Palenque
María Eugenia Petit-Breuilh Sepúlveda
Marina Ramos Serrano
José-Leonardo Ruiz Sánchez
Antonio Tejedor Cabrera

Review chairs of the 7th International Seminar on ORC Power Systems

Prof. Christoph Wieland (University of Duisburg-Essen) - *Review Chair*

Prof. Sotirios Karellas (National Technical University of Athens) - *Review Co-Chair*

Prof. Teemu Turunen-Saaresti (LUT University) - *Review Co-Chair*

Dr. Diego-César Alarcón-Padilla (Plataforma Solar de Almería - CIEMAT) - *Review Co-Chair*

Dr. Francesco Crespi (Universidad de Sevilla) - *Review Co-Chair*

Esta obra se distribuye con la licencia

Creative Commons Atribución-NoComercial-SinDerivadas 4.0 Internacional ([CC BY-NC-ND 4.0](#))



Usted es libre de:

Compartir — copiar y redistribuir el material en cualquier medio o formato

La licencianta no puede revocar estas libertades en tanto usted siga los términos de la licencia

Bajo los siguientes términos:

Atribución — Usted debe dar crédito de manera adecuada, brindar un enlace a la licencia, e indicar si se han realizado cambios . Puede hacerlo en cualquier forma razonable, pero no de forma tal que sugiera que usted o su uso tienen el apoyo de la licencianta.

NoComercial — Usted no puede hacer uso del material con propósitos comerciales .

SinDerivadas — Si remezcla, transforma o crea a partir del material, no podrá distribuir el material modificado.

No hay restricciones adicionales — No puede aplicar términos legales ni medidas tecnológicas que restrinjan legalmente a otras a hacer cualquier uso permitido por la licencia.

© Editorial Universidad de Sevilla 2024

c/ Porvenir, 27 - 41013 Sevilla.

Tlfs.: 954 487 447; 954 487 451; Fax: 954 487 443

Correo electrónico: info-eus@us.es

Web: <https://editorial.us.es>

© [David Tomás Sánchez Martínez](#) y [Lourdes García Rodríguez](#)
(coordinadores)

© De los textos, los autores 2024

ISBN 978-84-472-2745-7

DOI: <https://dx.doi.org/10.12795/9788447227457>

Diseño de cubierta y maquetación: los autores

INDEX OF CONTRIBUTIONS

ID3 - Additive manufacturing for fast prototyping of a velocity compounded radial re-entry turbine Authors: Dominik Stümpfl, Karel Ráž, Philipp Streit, Andreas P. Weiß.	13
ID4 - Thermodynamic concept of a novel recuperative two-phase power cycle process Authors: Benedikt G. Bederna, Riley B. Barta, Christiane S. Thomas.	23
ID7 - Performance analysis of a 1.5 MW Organic Rankine Cycle in a Carnot battery system for grid balancing services Authors: Robin Tassenoy, Hannes Van De Velde, Kenny Couvreur, Michel De Paepe, Steven Lecompte.	33
ID8 - Calibration of multi-hole probes for measurements in compressible organic vapor flows Authors: Leander Hake, Stephan Sundermeier, Stefan Aus Der Wiesche, Maximilian Passmann.	43
ID9 - pocketORC: A browser-based calculator for teaching organic Rankine cycle power systems Authors: Martin White.	53
ID10 - Evaluation of existing supercritical heat transfer correlations for designing the vapor generator in low-temperature transcritical Organic Rankine Cycle systems Authors: Jera Van Nieuwenhuyse, Anastasios Skiadopoulos, Dimitris Manolakos, Steven Lecompte, Michel De Paepe.	61
ID12 - A novel combined cooling and power cycle integrated ejector refrigeration and composition adjustment for stationary engine waste heat recovery Authors: Xiaocun Sun, Lingfeng Shi, Hua Tian, Gequn Shu.	71
ID14 - Design and construction of a reversible ORC test rig for geothermal CHP applications Authors: Florian Kaufmann, Christopher Schiffler, Christoph Wieland, Hartmut Spliethoff.	81
ID15 - Robust and fast meanline methodology for radial inflow turbines with non-ideal gases for system level optimisation of organic Rankine cycles Authors: Carola Freytag, Eva Alvarez-Regueiro, Pablo Ale-Martos, Esperanza Barrera-Medrano, Ricardo Martinez-Botas.	91
ID16 - Shape optimization of a sCO ₂ centrifugal compressor stage Authors: Alessandro Romei, Paolo Gaetani, Giacomo Persico.	101
ID17 - Optimizing the performance of a hybrid solar-biomass micro-CHP system with a TFC engine as the prime mover for domestic applications Authors: Anastasios Skiadopoulos, Xander Van Heule, Steven Lecompte, Michel De Paepe, Dimitrios Manolakos.	109
ID19 - Systematic and multi-criteria optimisation of subcritical thermally integrated Carnot batteries (TI-PTES) in an extended domain Authors: Antoine Laterre, Olivier Dumont, Vincent Lemort, Francesco Contino.	119

ID20 - ORC technology used in a heat removal system for an advanced nuclear power plant Authors: Guillaume Lhermet, Benoit Payebien, Nicolas Tauveron, Nadia Caney, Franck Morin	130
ID22 - Assessment of trilateral Organic Rankine Cycle for solar applications with innovative turboexpander concept Authors: Alessandro Romei, Andrea Giostri, Andrea Spinelli.	140
ID25 - Evaluation of the performance of an axial one-stage 10kW turbogenerator through experimental testing Authors: Piotr Klimaszewski, Piotr Klonowicz, Lukasz Witanowski, Tomasz Suchocki, Piotr Lampart, Eugeniusz Ihnatowicz, Lukasz Antczak, Dawid Zaniewski, Lukasz Jedrzejewski	149
ID26 - Investigation of the turbulence level and the vortex shedding in a turbine cascade working with an organic vapor at subsonic Mach numbers Authors: Leander Hake, Stephan Sundermeier, Stefan Aus Der Wiesche, Camille Matar, Paola Cinnella, Xavier Gloerfelt	159
ID27 - A novel approach to district heating: using a two-phase expander in a reversible heat pump-Organic Rankine Cycle system Authors: Sindu Daniarta, Attila R. Imre, Piotr Kolasinski	169
ID28 - Optimization of a partially evaporating Organic Rankine Cycle with thermal non-equilibrium expansion Authors: Xander Van Heule, Tasos Skiadopoulos, Dimitris Manolakos, Michel De Paepe, Steven Lecompte	176
ID29 - Cost-effective option of cold energy utilization in pharmaceutical industry Authors: Sindu Daniarta, Dawid Sowa, Ádám Havas, Attila R. Imre, Piotr Kolasinski	184
ID30 - Numerical investigation of a transonic dense gas flow over an idealized blade vane configuration Authors: Aurelien Bienner, Xavier Gloerfelt, Paola Cinnella, Leander Hake, Stefan Aus Der Wiesche	193
ID31 - Comprehensive analysis of ORC-VCC system for air conditioning from low-temperature waste heat Authors: Lukasz Witanowski	203
ID33 - Pareto front analysis for the design and the working fluid selection in ORC-based pumped thermal energy storage technology in both pure electric and cogenerative applications Authors: Marco Astolfi, Dario Alfani, Andrea Giostri	214
ID36 - Evaluating the waste heat sources in a very large crude carrier and the potential integration of Organic Rankine Cycle configurations Authors: Amalia Stainchaouer, Christopher Schiffler, Christoph Wieland, Hartmut Spliethoff	224
ID37 - Investigating R1234ze and R1234yf as replacements to R134a in waste heat recovery ORC applications Authors: James Bull, James Buick, Jovana Radulovic	234

ID38 - Performance and economic assessment of a thermally integrated reversible HP/ORC Carnot battery applied to data centers Authors: Chiara Poletto, Andrea De Pascale, Saverio Ottaviano, Olivier Dumont, Maria Alessandra Ancona, Michele Bianchi	244
ID39 - Evaluation of the performance of multiple supercritical CO ₂ power cycles in Waste Heat Recovery applications Authors: Hicham Chibli, Matthew Read, Abdalnaser Sayma	254
ID40 - Design and modeling of a demonstration-scale ORC cycle for the Liquid Air Combined Cycle Authors: Owen Pryor, William Conlon, Aaron Rimpel, Milton Venetos.....	264
ID41 - Guidelines and optimization criteria of a machine learning-based methodology for mixture design in ORC systems Authors: Valerio Mariani, Saverio Ottaviano, Andrea De Pascale, Giulio Cazzoli, Lisa Branchini, Gian Marco Bianchi	273
ID45 - Potential of trigenerative Waste Heat Recovery CO ₂ -mixture transcritical power plants for increasing the sustainability of district heating and cooling networks Authors: Mattia Baiguini, Michele Doninelli, Ettore Morosini, Dario Alfani, Gioele Di Marcoberardino, Paolo Giulio Iora, Giampaolo Manzolini, Costante Mario Invernizzi, Marco Astolfi	282
ID46 - Thermodynamic analysis of a novel pumped thermal energy storage system with waste heat integration Authors: Meiyang Zhang, Lingfeng Shi, Peng Hu, Gang Pei, Gequn Shu	294
ID48 - Pressure profile optimisation of a nozzle for wet-to-dry expansion Authors: Pawel Ogrodniczak, Abdalnaser Sayma, Martin T. White.....	304
ID51 - Thermodynamic modification of CO ₂ -based combined cooling and power cycle with ejector Authors: Yonghao Zhang, Lingfeng Shi, Gequn Shu	313
ID53 - Selection of suitable working fluid and storage material for ORC coupled with Thermal Energy Storage Authors: Dawid Sowa, Sindu Daniarta, Piotr Kolasinski	323
ID54 - Influence of dopant fluorination on the heat transfer behaviour of CO ₂ -based mixtures in transcritical power cycles Authors: Michele Doninelli, Gioele Di Marcoberardino, Costante Mario Invernizzi, Paolo Giulio Iora	333
ID57 - On air-cooled condensers for ORC systems operating with zeotropic mixtures Authors: Lorenzo Galieti, Carlo De Servi, Dario Alfani, Paolo Silva, Paola Bombarda, Piero Colonna	344
ID58 - Experiments on supersonic ORC nozzles in linear cascade configuration Authors: Marco Olivetti, Marco Manfredi, Giacomo Persico, Andrea Spinelli, Paolo Gaetani, Vincenzo Dossena	354
ID59 - Numerical analysis of aerodynamics and performance of a radial-inflow micro-ORC turbine Authors: Fatemeh Ardaneh, Marta Zocca, Antti Uusitalo, Teemu Turunen-Saaresti.	363

ID61 - ORC system using R1233zd(E) for waste heat recovery from the upstream process Authors: Meng Soon Chiong, Bemgba Nyakuma, Nur Izwanne Mahyon, Srithar Rajoo, Eva Alvarez-Regueiro, Maria Esperanza Barrera-Medrano, Ricardo F. Martinez-Botas, Yossapong Laoonual	373
ID63 - Experimental investigation of a small-scale reversible high temperature heat pump – Organic Rankine Cycle system for industrial Waste Heat Recovery Authors: Rahul Velanparambil Ravindran, Donal Cotter, Christopher Wilson, Ming Jun Huang, Neil Hewitt.	381
ID64 - Technical comparison and evaluation of a Pumped Thermal Energy Storage with two different designs Authors: Márcio Santos, Jorge André, Ricardo Mendes, José Ribeiro.	391
ID68 - The potential of CO ₂ -Plume Geothermal (CPG) Systems for CO ₂ component manufacturers: opportunities and development needs Authors: Christopher Schiffler, Jasper De Reus, Hartmut Spliethoff, Martin O. Saar, Sebastian Schuster, Dieter Brillert	400
ID69 - Development of a generalised low-order model for twin-screw compressors Authors: Florian Kaufmann, Ludwig Irrgang, Christopher Schiffler, Hartmut Spliethoff.	410
ID71 - Decision-making matrix for the selection of mixture in ORC applications Authors: William Combaluzier, Nicolas Tauveron, Michel Beaughon, Aldo Serafino.	420
ID72 - Reversible heat pump-ORC pilot plant – Experimental results and fluid charge optimization Authors: Maximilian Weitzer, Sebastian Kolb, Dominik Müller, Jürgen Karl	430
ID73 - Performance of Organic Rankine Cycle system in combination with residual municipal solid waste gasification: a simulation analysis Authors: Luca Cioccolanti, Giovanni Biancini, Ramin Moradi, Luca Del Zotto, Matteo Moglie	439
ID74 - Enhancing knowledge of engineering students at all levels on organic rankine cycle systems for their application in the built environment Authors: Luca Cioccolanti, Ramin Moradi, Ermira Abdullah, Syamimi Saadon, Mohamad Yusof Idroas, Teoh Yew Heng, Kwanchai Kraitong	449
ID75 - Studying carbon dioxide and acetone mixtures in a single-stage absorption-compression cycle for heating and cooling applications Authors: Jesús Gómez-Hernández, Ali Kholghi, Mercedes De Vega, Javier Villa, Ronan Grimes	458
ID77 - Valorising thermal composite recycling processes using Organic Rankine Cycles for combined heat and power applications Authors: Ramin Moradi, Liu Yang	466
ID80 – Prediction of the ideal maximum operational temperature of hydrocarbon and HFCs as working fluids of Organic Rankine Cycle power plants based on transition state theory Authors: Wei Yu, Chao Liu, Xijie Ban, Zhirong Li, Tianlong Yan	476
ID82 - Comparison of different evaporator topologies for industrial heat pumps Authors: Sanjay Vermani, Nitish Anand, Johan Van Bael, Evgueni Toulankine, Aldo Serafino, Carlo De Servi.	486

ID83 - On the plant improvement of Solar-driven ORC based power unit for domestic microcogeneration Authors: Fabio Fatigati, Marco Di Bartolomeo, Arianna Coletta, Diego Vittorini, Giammarco Di Giovine, Davide Di Battista, Roberto Cipollone.	496
ID84 - Mapping the techno-economic potential of next-generation CSP plants running on transcritical CO ₂ -based power cycles Authors: Pablo Rodríguez-deArriba, Francesco Crespi, Sara Pace, David Sánchez	505
ID86 - Achieving 45% micro gas turbine efficiency through hybridization with Organic Rankine Cycles Authors: Antonio Escamilla, David Sánchez Martínez, Lourdes García-Rodríguez	515
ID88 - Operational optimisation of the main heat rejection unit of CSP plants based on carbon dioxide mixtures Authors: Francesco Crespi, Pablo Rodríguez-deArriba, Lourdes García-Rodríguez, David Sánchez.	525
ID89 - Mechanical design and rotor-dynamic analysis of the ORCHID turbine Authors: Matteo Majer, Steven Chatterton, Ludovico Dassi, Alessio Secchiaroli, Edoardo Gheller, Carlo De Servi, Paolo Pennacchi, Piero Colonna, Matteo Pini.	535
ID91 - Thermodynamic feasibility of a pumped thermal energy storage driven by ocean temperature gradient Authors: Alessandra Ghilardi, Andrea Baccioli, Guido Francesco Frate, Lorenzo Ferrari	545
ID92 - Exergy-based methods for heat pumps Authors: Mathias Hofmann, Jonas Freißmann, Malte Fritz, Jeremias H. Alexe, Francesco Witte, George Tsatsaronis	553
ID93 - Reduced order modelling of optimized heat exchangers for maximum mass-specific performance of Airborne ORC Waste Heat Recovery units Authors: Fabio Beltrame, Dabo Krempus , Piero Colonna, Carlo De Servi.	563
ID97 - Basic design of an ORC demonstrator system for implementation in an Iron & Steel plant through the DECAGONE project Authors: Magnus Windfeldt, Han Deng, Trond Andresen, Christopher Schifflachner	574
ID98 - Analytical estimation of the presence of non-condensable gases in the condensate tank of an Organic Rankine Cycle Authors: Radheesh Dhanasegaran, Antti Uusitalo, Juha Honkatukia, Teemu turunen-Saaresti	584
ID101 - Advanced control of compressor inlet temperature in supercritical CO ₂ Brayton cycle Authors: Rui Wang, Xuan Wang, Hua Tian, Gequn Shu.	596
ID103 - Potential for surplus-heat-to-power conversion in current and future aluminium production processes with off-gas recycling Authors: Jonas Bueie, Magnus Windfeldt, Trond Andresen.	605
ID104 - Investigating the application range of ORC power plants for the exploitation of two-phase geothermal resources Authors: Tristan Merbecks, Claudio Pietra, Paola Bombarda, Martin O. Saar, Paolo Silva, Dario Alfani.	615
ID109 - Cold Energy Recovery in LNG plants with Organic Rankine Cycle Authors: Gabriele Marchiori, Marta Giudici, Giorgia Ruffato, Marco Astolfi	626

ID110 - Numerical investigation of organic vapor flow effects on a micro-scale radial turbocompressor Authors: Andrés Sebastián, Rubén Abbas, Manuel Valdés	636
ID112 - Design, modeling and simulation of an experimental Rankine PTES system Authors: Mario Petrollese, Giorgio Cau, Matteo Marchionni, Marcello Lorenzo Marroccu, Rosa Merchan	645
ID113 - Small-scale turbopumps for Waste Heat Recovery applications based on an Organic Rankine Cycles, modeling, analytical and experimental investigation Authors: Sajjad Zakeralhoseini, Jürg Schiffmann	655
ID116 - Double-stage ORC system based on various temperature waste heat sources of the negative CO2 power plant Authors: Kamil Stasiak, Pawel Ziolkowski, Dariusz Mikielewicz	665
ID117 - Optimization of organic Rankine cycle in ocean thermal energy conversion based on NSGA-II Authors: Zheng Hu, Jiufa Chen, Bing Guo, Chengbin Zhang	679
ID118 - TES4Trig: Development of a demonstrator for the production of electricity, heating and cooling based on an Organic Rankine and an Ejector Cooling Cycle driven by high-temperature parabolic trough collectors with thermal energy storage Authors: Konstantinos Braimakis, Dimitrios Tziritas, George Stavrakakis, Julio Terrón Gutiérrez, Siddhart Dutta, Christos Xynos, Panagiotis Zervas, Sotirios Karellas	689
ID119 - Simulation and operation of a CSP that works with a HRB Cycle Authors: Antonio J. Subires, Antonio Rovira	701
ID123 - Towards a green energy community: integration of micro-ORCs combined with renewable energy technologies in buildings Authors: Diego Antonio Rodríguez Pastor, Víctor Manuel Soltero Sánchez, Elisa Carvajal Trujillo, José Antonio Becerra, Ricardo Chacartegui	713
ID129 - Assessment of high temperature heat pump layouts equipped with a bladeless turboexpander Authors: Matteo Passalacqua, Simone Maccarini, Stefano Barberis, Alberto Traverso	723
ID133 - Selection of the optimal working fluid in an Organic Rankine Cycle for Waste Heat Recovery through multi-objective optimization and decision making Authors: Bipul Krishna Saha, El Mouatez Billah Messini, Syed J. Hoque, B Aneesh Bhat, Pramod Kumar	733
ID139 - Dual condensing pressure ORC for cryogenic energy storage Authors: William M. Conlon, Milton J. Venetos	743
ID141 - Optimum coupling of thermal energy storage and power cycles for Carnot batteries Authors: Salvatore Guccione, Rafael Guede	751
ID142 - Aerodynamic design and numerical analysis of a counter-rotating centrifugal compressor Authors: Cheikh Brahim Abed, Arthur Leroux	761

TES4TRIG: DEVELOPMENT OF A DEMONSTRATOR FOR THE PRODUCTION OF ELECTRICITY, HEATING AND COOLING BASED ON AN ORGANIC RANKINE CYCLE AND AN EJECTOR COOLING CYCLE DRIVEN BY HIGH-TEMPERATURE PARABOLIC TROUGH COLLECTORS WITH THERMAL ENERGY STORAGE

Konstantinos Braimakis^{1,*}, Dimitrios Tziritas², George M. Stavrakakis², Julio Terrón Gutiérrez³,
Siddharth Dutta⁴, Christos Xynos⁵, Panagiotis Zervas², Sotirios Karellas⁵

¹ *Laboratory of Refrigeration, Air Conditioning & Solar Energy
National Technical University of Athens, Athens, Greece*

² *MES ENERGY S.A., Athens, Greece*

³ *CADE Soluciones de Ingeniería, S.L., Parque Científico y Tecnológico de Albacete, Albacete, Spain*

⁴ *Protarget A.G., Cologne, Germany*

⁵ *Laboratory of Thermal Processes
National Technical University of Athens, Athens, Greece*

*Corresponding Author: mpraim@central.ntua.gr

ABSTRACT

This study presents the development of the TES4Trig demonstrator that will be installed for covering the energy needs of the Administration building of the Lavrio Technological and Cultural Park (LTCP) in Attica, Greece within TES4Trig CSP-ERANET project. The system is driven by high-temperature parabolic trough collectors (PTC) coupled with innovative solid-state thermal energy storage (TES). Heat is supplied to an Organic Rankine Cycle (ORC) – Ejector cooling cycle (ECC) through a heat transfer fluid (HTF). The ORC-ECC is capable of the following operating modes: 1) electricity-only, 2) combined heat and power (CHP) and 3) cooling. The system energy production and consumer demand were considered for the conceptual design and preliminary definition of the operating strategies of the ORC-ECC. The final design of the ORC-ECC system is based on the use of R1233zd(E) as a working fluid, operating at a maximum temperature of 140°C.

1 INTRODUCTION

As of 2023, the vast majority of existing commercial concentrating solar power (CSP) plants (97 out of 105) are based on Steam Rankine Cycle (SRC) and are oriented toward large power capacities above 10 MW_e (IRENA, 2022). Despite the significant development of the technology in the last decades, the economics of CSP is still unfavorable, as it is associated with the highest levelized cost of electricity (LCOE) among other renewable power generation technologies, mainly due to its high capital investment cost (CAPEX).

Two main strategies to increase the cost-effectiveness of CSP plants include the increase of their thermal energy storage (TES) capabilities to improve their capacity factor as well as polygeneration, to produce heating and/or cooling in addition to electrical energy and thus increase their revenue. The latter option is usually infeasible in the case of large CSP plants that are typically located in remote locations (for example in desert areas) far from heating and cooling consumers because of their significant land requirement linked with their low energy density (77 kWh_e/m²/year) (Lovering et al., 2022). Meanwhile, cost-effective, long-term TES technologies are needed to make CSP plants competitive against utility PV which typically include electrical batteries of limited storage capacity. Considering the above, polygeneration CSP plants at smaller scales that could service building energy consumers combined

with cost-effective TES could have significant market potential and improve the share of CSP in the energy mix.

At smaller scales, the Organic Rankine Cycle (ORC) is more suitable for thermal power generation than SRC, making it attractive for small-scale CSP plants. One of the most typically considered solar collector technology for such plants is parabolic trough collectors (PTCs), which offer good efficiencies at high heat transfer fluid (HTF) temperatures, up to 400°C (Kalogirou, 2023)(Kalogirou, Karellas, Badescu, et al., 2016; Kalogirou, Karellas, Braimakis, et al., 2016). Furthermore, in the last years, the cost of PTCs is declining, presenting opportunities for increasing the cost-competitiveness of the technology (Kurup & Turchi, 2015).

PTC-driven ORC plants for exclusive electricity production or polygeneration based on parabolic trough collectors (PTCs) have been extensively investigated at a theoretical level from a thermodynamic and techno-economic perspective. However, very few examples of experimental prototypes and real-world plants are available, especially considering polygeneration (Kasaeian et al., 2022). Aiming to fill this gap, this study presents the conceptual design and definition of the main operating strategies and main technical specifications of the TES4Trig demonstrator plant (TES4Trig Project, 2023), which will consist of a small-scale, PTC-driven ORC coupled with an ejector cooling cycle (ECC) into a singular ORC-ECC system for the production of electricity, heating and cooling. The demonstrator will also feature an innovative solid-state TES. The demo will service the energy needs of the Administration “Serpieri” Building of Lavrio Technological and Cultural Park (LTCP) in Attica, Greece in the context of a project funded by CSP ERANET (CSP ERANET, 2023).

2 TES4TRIG CONCEPTUAL DESIGN

2.1 Description of the demo site

The TES4Trig demo will be installed to cover the energy needs of the Administration (Admin) “Serpieri” building of the LTCP. The building houses several offices, seminar rooms and library/archive rooms. The area considered for installing the prototype is located at the west of the Admin building, which is sufficiently large for the installation of the solar field of the system. The Admin building was built in 1875 and has high symbolic and architectural value. As a result, great care had to be taken to ensure the harmonious integration of the TES4Trig system with them.

2.2 Heating, cooling and electrical energy demands

At present, the building’s heating and cooling system consists of a heating oil boiler and a chiller and a hydronic distribution system to deliver hot/chilled water to the building terminal units (fan coil units-FCUs). The boiler has an average capacity of 93.04 kW_{th} and a maximum capacity of 125 kW_{th}. The chiller is a type HRA 0252 model from Climaveneta with a nominal cooling capacity of 61.6 kW_c.

For the needs of the project, the hourly variation of the heating and cooling demand of the building was calculated for 12 characteristic days of the year, each corresponding to a different month. Note that the electricity loads were not a critical factor in the design of the TES4Trig system because its scale is significantly lower than the electricity loads of the building. For the calculation of the heating load, DIN 4701 standard was implemented (DIN, 1995a, 1995b). For the calculation of the cooling load, CLTD/CLF method was implemented (ASHRAE, 1985). The hourly variation of the heating and cooling load of the building for the characteristic day of each month of the heating and cooling periods is illustrated in the diagrams of **Figure 1**.

The maximum heating demand occurs in January at 9:00 am and is about 70 kW_{th}. Generally, the maximum heating demand appears early in the morning, when the building occupants arrive and gradually declines until noon, owing to the solar radiation heat gains. Right after noon, as many of the building areas are not used, the demand abruptly declines, remaining approximately constant until 16:00, at which all users of the building leave.

As far as cooling demand is concerned, its maximum value is around 73 kW_c and occurs near noon in the summer months (July and August). Like the heating demand, the cooling demand abruptly declines after noon. According to calculations, the total annual heating, cooling and electricity demand are equal to 17580 kWh/year, 22720 kWh/year and 11540 kWh/year, respectively.




Figure 1: Heating (left) and cooling (right) loads for the characteristic day of each month

2.3 Parabolic trough collectors field

The solar field size was predetermined at the start of the project. It consists of two arrays of a total of 8 modules (4 modules/array) of single-axis tracking PTCs, each having an aperture of about 150 m² (total aperture of solar field is about 300 m²). The PTCs are installed in an approximately N-S orientation, which is preferable for maximizing the annual solar thermal power production based on the available plot of land. The gross land surface occupied by the solar field (considering also necessary spacing of PTC arrays) is about 600 m². The peak and average solar thermal power output, as well as the generated energy by the solar field for the two corresponding to maximum (summer) and minimum (winter) solar irradiance throughout the year, are summarized in **Table 1**. The PTC field is capable of a maximum operating HTF temperature of about 400 °C. The project partner responsible for the development and manufacturing and installation of the solar field is the German industrial company Protarget AG (Protarget AG, 2023).

Table 1: Solar field main specifications

	Peak power (kW)	Average power 08:00 – 18:00 (kW _{th})	Generated energy (kWh _{th})
Summer	125	100	1000
Winter	90	51	510

2.4 Thermal energy storage

The TES, developed by project partner CADE Engineered Technologies (CADE Engineered Technologies, 2023) works in parallel with the PTC field and the ORC-ECC (**Figure 2**). Normally, when the solar power produced by the solar field is greater than the thermal demand of the ORC-ECC, the surplus solar power is stored in the TES. On the other hand, when the ORC-ECC thermal demand is higher than the solar power produced by the solar field, thermal energy is supplied from the TES to the ORC-ECC.




Figure 2: Simplified TES4Trig block diagram

2.5 ORC-ECC

The ORC-ECC system consists of an ORC coupled with an ECC. A recuperative ORC is implemented. The ECC is a thermally-driven cooling cycle, which is applied for the production of cooling through the exploitation of thermal energy and has been widely considered as a solar cooling technology (Braumakis, 2021). It is similar to the conventional vapor compression cycle; however, the mechanical compression of the latter is replaced by a dynamic compression occurring in an ejector device. In the TES4Trig project, an innovative ORC-ECC configuration is designed, which consists of an ORC coupled with an ECC. Both cycles run with the same working fluid and use a common heat exchanger as an ORC evaporator/ECC generator, as well as a common condenser, subcooler and pump.

The ORC-ECC has three operating modes: 1) electricity-only, 2) combined heat and power (CHP), and 3) cooling-only. In the first two modes, only the ORC is operational, while in the third mode, only the ECC is operational. In electricity-only mode, the ORC working fluid is heated in the ORC evaporator, passes through the expander, the recuperator hot-side and subsequently through the condenser and subcooler, exiting it as subcooled liquid which is then discharged by the ORC pump to the recuperator's cold-side. The CHP mode is similar, however, in this mode, the recuperator is bypassed and the condenser pressure/temperature is raised to produce heat at higher temperature. In cooling mode, the working fluid exiting the ORC evaporator is driven to the high-pressure inlet port of the ejector where it is mixed with low-temperature and pressure vapor coming from the ECC (cooling) evaporator that enters the low-pressure port of the ejector. In the ejector, the two streams are mixed and the resulting mixed vapor stream leaves the ejector at an intermediate pressure from its outlet port and is supplied to the condenser and subcooler. The subcooled liquid stream is pressurized in the pump and split into two streams. The first is conveyed to the ORC evaporator and the second to the ECC cooling evaporator.

A simplified schematic of the ORC-ECC configuration for the three different operating modes is shown in **Figure 3**. In each layout, the active sections of the system in each mode are highlighted. Note that the schematics shown in this figure are conceptual and do not represent the actual system. For each mode, the processes occurring are illustrated in temperature-entropy diagrams shown in the same figure.

2.6 -Integration of ORC-ECC with consumer building

The ORC-ECC system will be integrated into the existing heating and cooling building infrastructure through an intermediate water-glycol circuit, which is used for the interconnection between the refrigerant circuit (ORC-ECC) and the hydronic distribution network of the building. The water-glycol circuit includes a heating heat exchanger (for the provision of heating), a cooling heat exchanger (for the provision of cooling) and a dry cooler, which is used for rejecting excess heat to the ambient, as shown in **Figure 4**.

As it will be shown next, the cooling produced by the ECC is much smaller than the cooling demand of the building. Therefore, all cooling produced by the ECC is fully utilized. On the other hand, the heating produced by the ORC in CHP mode is comparable to the heating demand of the building. Consequently, because the heating demand of the building fluctuates, the flow rate of the water-glycol being supplied to the heating heat exchanger is adjusted through a three-way valve, while the remaining water-glycol flow is rejected through the dry cooler. At all times, the oil boiler and chiller of the building operate as auxiliary systems.




Figure 3: ORC-ECC layout and thermodynamic processes occurring in electricity-only mode (top), CHP mode (middle) and cooling mode (bottom)

3 TECHNICAL SPECIFICATIONS AND OPERATING STRATEGIES

3.1 Main technical specifications of ORC-ECC system

For the ORC-ECC, it was decided to use hydrofluoroolefin R1233zd(E) as a working fluid (Honeywell, 2018), as it is non-toxic, non-flammable and environmentally friendly (Bramakis et al., 2017). One of its drawbacks is its relatively lower efficiency for use in ORCs and ECCs because it has a lower critical temperature (167°C) and the fact that its maximum operating temperature is relatively limited to below

150-180°C because of its thermostability (Kim et al., 2018). Notably, the use of the particular low-critical temperature fluid instead of a working fluid of higher critical temperature (such as a hydrocarbon or siloxane) that would result in higher cycle efficiencies in the particular application which is driven by high-temperature PTCs is sub-optimal (Bramakis et al., 2017). Nevertheless, the safety of operation was prioritized over efficiency in the demonstrator because of its special characteristics (non-industrial environment, within a historical site and next to a building that is used as an office by non-trained personnel). Because of the aforementioned limitations, the maximum ORC-ECC cycle temperature was limited to 140°C. The detailed design specifications of the ORC-ECC for the three main operating modes are summarized in **Table 2**. The design specifications were determined by modeling the system in Matlab (*MATLAB - MathWorks*, 2023), using REFPROP (Huber et al., 2022) for the calculation of all thermophysical properties and the 1-D ejector model by Huang et al. (Huang et al., 1999). Briefly, in the electricity-only and CHP modes, the cycle's maximum temperature is 135 °C and a superheating degree of 10 K is applied, while the condensation temperature is 21/40°C (winter/summer) and 55°C, respectively. Regarding the ECC, the maximum cycle temperature is slightly increased to 140°C and a lower superheating degree is applied (5 K), while a condensation temperature of 45°C is assumed.




Figure 4: Simple schematic of the integration layout of the ORC-ECC with the building

Critical limitations regarding the ORC upper and lower pressure selection arise because of expander limitations at the targeted power range (about 5-20 kW). In the project, two similar twin-screw expanders with different built-in volume ratios will be used, which are modified commercial compressor models produced by Bitzer. The first is an OSK-5361 model (built-in volume ratio=3.5) that had been used in a past experimental test rig by TUM (Dawo et al., 2021) and the second is an OSN-5361 model (built-in volume ratio 5.6) offered to NTUA by Bitzer (Bitzer, 2023)(TAIRIS AEBE, 2023).

In the following equations, the basic performance indexes are presented based on which the efficiency of the whole system is calculated.

The heat supplied to the ORC-ECC :

$$\dot{Q}_{in} = \dot{m}_{HTF} \cdot (h_{HTF}^{in} - h_{HTF}^{out}) = \dot{m}_{WF} \cdot (h_2 - h_1) \quad (1)$$

The net electric power produced by the ORC is given by the following equation:

$$P_{e,net} = \dot{m}_{WF} \cdot \left[(h_3 - h_4) \cdot \eta_{em} - \frac{(h_1 - h_6)}{\eta_{pump}} \right] \quad (2)$$

The cooling output in the ECC evaporator is given by the following equation:

$$\dot{Q}_c = \dot{m}_{WF} \cdot (h_8 - h_7) \quad (3)$$

The useful heat produced by the condenser in CHP mode is given by the following equation:

$$\dot{Q}_h = \dot{m}_{WF} \cdot (h_5 - h_6) \quad (4)$$

The two main performance indexes of the system are the electric efficiency of the ORC and the thermal coefficient of performance (COP) of the ECC. These are defined according to the following equations:

$$\eta_e = \frac{P_{e,net}}{\dot{Q}_{in}} \quad (5)$$

$$COP_{th} = \frac{\dot{Q}_c}{\dot{Q}_{in}} \quad (6)$$

3.2 Sizing and operating strategies

The starting point for sizing the TES4Trig demonstrator and the definition of its operating strategies was the size of the solar field (determined a priori) and the heating/cooling demand of the building. For the needs of the project, two objectives were prioritized: 1) high annual solar energy utilization, and 2) covering substantial shares of the heating and cooling demand of the building, while also producing as much electrical energy as possible. The following operating strategy was thus defined for the preliminary sizing of the ORC-ECC system:

- Throughout the whole year, the ORC-ECC is operational whenever sufficient thermal power is available either from the solar field or from the TES.
- To ensure the reliability of operation, the ORC operates under a relatively constant thermal input (corresponding to the design thermal input point) with a cut-off threshold of 75% of the design. On the other hand, the ECC operates exclusively at the design point. Meanwhile, the operating mode of the ORC-ECC (and thus the produced useful energy) changes depending on the demand status of the building between electricity-only, CHP and cooling modes.
 - When there is neither heating nor cooling demand, the ORC-ECC produces electricity.
 - When there is heating demand, the ORC-ECC operates in CHP mode. If the produced heat is higher than the heating demand, the excess heat generated in the condenser is rejected to the ambient through the dry cooler. If the produced heat is lower than the heating demand, the ORC-ECC provides all the heat it can to the building and the remaining heat demand is covered by the oil boiler.
 - When there is cooling demand, the ORC-ECC operates in ECC mode. Since the cooling output of the ECC is much lower than the cooling demand, all produced cooling is utilized for covering the cooling demand of the building, while the remaining cooling demand is covered by the chiller of the building.

Table 2: ORC-ECC design specifications

Parameter	Electricity-only	CHP	Cooling-only
HTF inlet/outlet temperature (°C)		400/350	
Maximum working fluid temperature (°C)	135		140
Maximum fluid pressure (bar)	17.4		20.9
Working fluid superheating degree at ORC evaporator/ECC generator outlet (K)	10		5
Expander model used	OSN-5361 (winter) OSK-5361 (summer)	OSK-5361	-
Condensation temperature (°C)	21 (winter) 40 (summer)	55	45
Cold stream temperature rise in recuperator (K)	30 (winter) 20 (summer)	0	25
Cooling evaporator saturation temperature (°C)	-		5
Cooling evaporator superheating degree (K)	-		2
Subcooling degree at pump inlet (K)		5	
Expander isentropic efficiency (%)	65		-
Generator electromechanical efficiency (%)	96		
Pump isentropic efficiency (%)		65	
Pump motor electromechanical efficiency		85	
Water-glycol temperature at ECC evaporator inlet/outlet (°C)			13/8
Hot/chilled water return/supply temperature to/from building hydraulic network (°C)	-	47/52(hot water)	18/17.4 (chilled water)
Water-glycol temperature at condenser inlet/outlet (°C)	13/18 (winter) 32/47 (winter)	47/52	37/42
ORC electric efficiency (%)	13.6 (winter) 10.7 (summer)	8.9	-
Heating efficiency (%)	-	87.4	-
ECC ejector entrainment ratio (-)	-		0.13
ECC thermal COP (-)	-		0.10

Regarding the thermal input to the ORC-ECC by the solar field and TES, the following operating strategy is applied:

- If there is no sun (no SF solar thermal power - $\dot{Q}_{SF} = 0$) the following cases are distinguished:
 - If the available thermal power from the TES ($\dot{Q}_{TES} = 0$) is lower than the minimum required by the ORC-ECC ($\dot{Q}_{min}$), the TES is idle while the ORC-ECC is not operational (**No operation mode**).
 - If the available thermal power from the TES is higher than the minimum required by the ORC-ECC ($\dot{Q}_{TES} > \dot{Q}_{min}$), the TES drives the ORC-ECC (**TES production and discharge mode**). The following cases are distinguished regarding the ORC-ECC:
 - If the available thermal power from the TES is lower than the nominal required by the ORC-ECC ($\dot{Q}_{nom} > \dot{Q}_{TES} > \dot{Q}_{min}$), the ORC-ECC operates in part-load (**TES production and discharge mode A**).

- If the available thermal power from the TES is higher than the nominal required by the ORC-ECC ($\dot{Q}_{TES} > \dot{Q}_{nom}$), the ORC-ECC operates in full load (**TES production and discharge mode B**).
- If there is sun ($\dot{Q}_{SF} > 0$) the following cases are distinguished:
 - If the SF solar thermal power is lower than the minimum required by the ORC-ECC ($\dot{Q}_{SF} < \dot{Q}_{min}$), the following cases are distinguished:
 - If the sum of the SF solar thermal power and available thermal power from the TES is lower than the minimum required by the ORC-ECC ($\dot{Q}_{SF} + \dot{Q}_{TES} < \dot{Q}_{min}$), the ORC-ECC is not operational and the TES is charged (**Charge mode**).
 - If the sum of the SF solar thermal power and the available thermal power from the TES is higher than the minimum required by the ORC-ECC but lower than the nominal ($\dot{Q}_{nom} > \dot{Q}_{SF} + \dot{Q}_{TES} > \dot{Q}_{min}$), the ORC-ECC operates in part-load and is driven by both the SF and TES (**SF-TES production and discharge mode**).
 - If the SF solar thermal power is higher than the minimum required by the ORC-ECC but lower than the nominal ($\dot{Q}_{nom} > \dot{Q}_{SF} > \dot{Q}_{min}$), the SF solar thermal power is used for driving the ORC-ECC, which operates in part-load. No heat is stored (**SF production mode**).
 - If the SF solar thermal power is higher than the nominal required by the ORC-ECC ($\dot{Q}_{SF} > \dot{Q}_{nom}$), the needed SF solar thermal power is used for driving the ORC-ECC while the surplus solar thermal power ($\dot{Q}_{SF} - \dot{Q}_{nom}$) is stored in the TES (**SF production and charge mode**).

In the flowchart of **Figure 5** the described operation strategy is illustrated.




Figure 5: Flowchart of the operating strategy

3.3 TES4Trig demonstrator overall conceptual design and operating strategies

Based on the aforementioned considerations, the ORC-ECC was sized based on a nominal thermal input of 75 kW_{th}, equal to the nominal thermal power capacity of the TES, which will have a total energy storage capacity of 400 kWh_{th}. Based on the specifications shown in **Table 2**, the power, heating and cooling output of the system is presented in **Table 3**.

Table 3: Electric power, heating and cooling output of TES4Trig system (nominal)

Parameter	Electricity-only	CHP	Cooling-only
Electric power output (kW _e)	10.2 (winter) 8.0 (summer)	6.7	-
Heating output (kW _{th})	-	65.6	-
Cooling output (kW _c)	-	-	7.7

3.4 Experimental validation and challenges

The commissioning of the prototype is planned for Q1 2024. Commissioning tests are necessary to fully define the control of each subsystem and the overall prototype. Following commissioning, the prototype will be demonstrated for the following years to evaluate its performance under variable conditions of solar availability for different cases of the building energy demand for all operational modes.

To date, the most challenging aspect of the project is the integration of the prototype into the consumer building. Because of the architectural and historical value of the building, great care had to be taken to minimize aesthetic disruption of the location. This necessitated the development of a very long underground channel to house piping and cables (power supply, automation) since it was not acceptable to carry out any non-reversible interventions on the building itself. Secondly, integration challenges arise because of the sophisticated automation, large number of equipment components (valves, sensors) and complexity of the piping interconnection layout with the existing infrastructure of the building, considering all different operating modes and the need for providing heating and cooling at specific temperatures. An additional challenge is the development of fully automated control, which should orchestrate all different subsystems of the prototype (solar field, thermal energy storage, ORC-ECC) as well as the consumer building itself.

Regarding the ORC-ECC, the major challenge was the difficulty of developing a micro-scale ORC to be driven by a very high-temperature heat source, which was the original scope of the project. This is because of several reasons. First, there is currently very limited (if any) availability of micro-scale expansion machines capable of operating at very high temperatures above 140°C. Secondly, because of the installation of the prototype in a non-industrial site, safety precautions dictated the use of non-flammable working fluids, excluding the use of alkanes which are suitable for high temperatures. As a result, the system was eventually designed for operation at a maximum temperature of 140°C. This decision required the use of a sophisticated, tailor-made evaporator, because of the significantly high-temperature difference between the working fluid and the HTF.

4 CONCLUSIONS

In the present work, the conceptual design, operating strategy and sizing of the TES4Trig prototype and its subsystems were described. The system will be installed for covering the energy needs of the Admin building of the Lavrio Technological and Cultural Park (LTCP).

NOMENCLATURE

Abbreviations

CHP	Combined Heat & Power
ECC	Ejector Cooling Cycle
HTF	Heat Transfer Fluid
LTCP	Lavrio Technological and Cultural Park
ORC	Organic Rankine Cycle
PTC	Parabolic Trough Collectors
SF	Solar Field
TES	Thermal Energy Storage

Variables

COP	Coefficient of performance	(-)
h	specific enthalpy	(kJ/kg)
$\dot{m}$	mass flow rate	(kg/s)
P	power	(kW)
$\dot{Q}$	heat duty	(kW)

Greek letters

η	efficiency	(-)
--------	------------	-----

Subscript

c	cooling
e	electric
em	electromechanical (expander-generator)
h	heating
HTF	heat transfer fluid
in	input, inlet
min	minimum thermal power required for driving the ORC-ECC
n	net
net	net
nom	nominal thermal power required for driving the ORC-ECC
out	outlet
pump	pump
SF	thermal power produced by solar field
TES	thermal power available from thermal energy storage
th	thermal
WF	working fluid

REFERENCES

- ASHRAE. (1985). *American Society of Heating, Refrigerating and Air-Conditioning Engineers, 1985 ASHRAE Handbook: Fundamentals*, Atlanta: American Society of Heating, Refrigerating and Air-Conditioning Engineers, 1985.
- Bitzer. (2023). BITZER. <https://www.bitzer.de/gb/en/>
- Braimakis, K. (2021). Solar ejector cooling systems: A review. *Renewable Energy*, 164, 566–602. <https://doi.org/10.1016/j.renene.2020.09.079>
- Braimakis, K., C. Roumpedakis, T., Leontaritis, A.-D., & Karellas, S. (2017). Comparison of Environmentally Friendly Working Fluids for Organic Rankine Cycles. *Advances in New Heat Transfer Fluids*, 377–426. <https://doi.org/10.1201/9781315368184-13>
- CADE Engineered Technologies. (2023). <https://cadeengineering.com/>.
- CSP ERANET. (2023). <https://csp-erant.eu/results/thermal-energy-storage-demand-solar-trigeneration-tes4trig>.
- Dawo, F., Eyerer, S., Pili, R., Wieland, C., & Spliethoff, H. (2021). Experimental investigation, model validation and application of twin-screw expanders with different built-in volume ratios. *Applied Energy*, 282, 116139. <https://doi.org/10.1016/J.APENERGY.2020.116139>
- DIN. (1995a). *DIN 4701-1 Rules for calculating the heat load of buildings- Part 1: Basic rules for calculation*.
- DIN. (1995b). *DIN 4701-2 Rules for calculating the heat requirement of buildings - Part 2: Tables, pictures, algorithms*.
- Honeywell. (2018). *A Better Environment with Next-Generation Solstice® and Refrigerant Solstice zd: Compliant with Regulations*.
- Huang, B. J., Chang, J. M., Wang, C. P., & Petrenko, V. A. (1999). A 1-D analysis of ejector performance. *International Journal of Refrigeration*, 22(5), 354–364. [https://doi.org/10.1016/S0140-7007\(99\)00004-3](https://doi.org/10.1016/S0140-7007(99)00004-3)
- Huber, M. L., Lemmon, E. W., Bell, I. H., & McLinden, M. O. (2022). The NIST REFPROP Database for Highly Accurate Properties of Industrially Important Fluids. *Industrial and Engineering Chemistry Research*, 61(42), 15449–15472. <https://doi.org/10.1021/ACS.IECR.2C01427>
- IRENA. (2022). *Renewable Power Generation Costs in 2021*.
- Kalogirou, S. A. (2023). *SOLAR ENERGY ENGINEERING : processes and systems*.
- Kalogirou, S. A., Karellas, S., Badescu, V., & Braimakis, K. (2016). Exergy analysis on solar thermal systems: A better understanding of their sustainability. *Renewable Energy*, 85, 1328–1333. <https://doi.org/10.1016/J.RENENE.2015.05.037>

- Kalogirou, S. A., Karellas, S., Braimakis, K., Stanciu, C., & Badescu, V. (2016). Exergy analysis of solar thermal collectors and processes. *Progress in Energy and Combustion Science*, 56, 106–137. <https://doi.org/10.1016/J.PECS.2016.05.002>
- Kasaeian, A., Mirjavadi, K., Pourmoghadam, P., Asgari Sima, F., Amirhaeri, Y., Borhani, S., & Fereidooni, L. (2022). Organic Rankine cycles powered by parabolic trough collectors: An overview. *Sustainable Energy Technologies and Assessments*, 54, 102847. <https://doi.org/10.1016/J.SETA.2022.102847>
- Kim, S., Rached, W., & Abbas, L. (2018). Performance and Stability of E-1233zd in Energy Recovery Applications. *International Refrigeration and Air Conditioning Conference*. <https://docs.lib.purdue.edu/iracc/2053>
- Kurup, P., & Turchi, C. S. (2015). *Parabolic Trough Collector Cost Update for the System Advisor Model (SAM)*. <https://doi.org/10.2172/1227713>
- Lovering, J., Swain, M., Blomqvist, L., & Hernandez, R. R. (2022). Land-use intensity of electricity production and tomorrow's energy landscape. *PLOS ONE*, 17(7), e0270155. <https://doi.org/10.1371/JOURNAL.PONE.0270155>
- MATLAB - MathWorks. (2023). <https://www.mathworks.com/products/matlab.html>
- Protarget AG. (2023). <https://protarget-ag.com/>.
- TAIRIS AEBE. (2023). Ταΐρης AEBE – Κορυφαίες λύσεις ψύξης, κλιματισμού & θέρμανσης σε όλους τους κλάδους την βιομηχανίας. <https://www.tairis.gr/en/enhome/>
- TES4Trig Project. (2023). *Thermal Energy Storage for On-demand Solar Trigenation (TES4Trig)*, <http://www.solar.demokritos.gr/ERANET/>.

ACKNOWLEDGEMENT

The study has been funded by the TES4Trig project within the CSP ERANET 1st Joint Call.

This book contains the compilation of works contributed to the *7th International Seminar on Organic Rankine Cycle Power Systems* (ORC 2023), held in Seville between the 4th and 6th of September 2023. The event was hosted by Universidad de Sevilla on behalf of the Knowledge Centre on Organic Rankine Cycle Technology (KCORC), incorporated in The Netherlands.

The ORC conference, organized biennially, stems as the only conference that is specific to ORC technology, therefore gathering a diverse community whose affiliation spans across all the interested stakeholders, not only in this particular technology but also and in a broader context, in the energy transition. Original equipment manufacturers, professional associations, end-users, investors, policy makers, academics, scientists feel at home at ORC 2023.

The almost 100 proceedings in this book cover a wide variety of topics, from fundamentals to system integration through component design, accounting for thermodynamic performance as well as component design. In addition to this, and as a new track in 2023, works on heat pump technology were also accepted in order to raise awareness of the strong ties between both technologies, specifically in energy storage applications.

This book provides an excellent overview of the current maturity of power systems based on Organic Rankine Cycle technology for applications as diverse as geothermal and waste heat recovery in industry or downstream of other prime movers (e.g., marine applications). It is also an excellent source of information to understand the current challenges faced by the technology, stemming from a very competitive market and increasingly stringent environmental regulations.

The organizers of ORC 2023 hope that the reader finds this work as exciting as the attendees to the conference and, maybe, make the decision to join the 8th edition to the conference in 2025.